



Product Service

CERTIFICATE

No. B 022757 1155 Rev. 00

Holder of Certificate: **HAGS Aneby AB**
Grännavägen 7
578 23 Aneby
SWEDEN

Certification Mark:



Product: **Slides**
Slide part 2

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713276464-9

Valid until: 2028-01-29

Date, 2023-02-14

(Michael Weber)

CERTIFICATE

No. B 022757 1155 Rev. 00

Model(s):

SL-1000S, SL-1500S, SL-2000S, SL-2500S, SL-3000S,
SL-1000SH, SL-1500SH, SL-2000SH, SL-2500SH, SL-3000SH,
SL-1000D, SL-1500D, SL-2000D, SL-2500D, SL-3000D,
SL-1000DH, SL-1500DH, SL-2000DH, SL-2500DH, SL-3000DH
HAGS Stair - Embankment Steps: Steps single handrail,
Steps double handrail

Parameters:

The embankment Slides are made of 2 mm thick S304 grade stainless steel.

Single Width Slides, 350 mm Wide; Slides Only (SL-XXXXS)
1000 mm high, 30° slope - SL-1000S
1500 mm high, 30° slope - SL-1500S
2000 mm high, 30 - 35° slope - SL-2000S
2500 mm high, 30 - 35° slope - SL-2500S
3000 mm high, 30 - 35° slope - SL-3000S

Single Width Slides, 350 mm Wide; Slides & Handrail (SL-XXXXSH)
1000 mm high, 30° slope - SL-1000SH
1500 mm high, 30° slope - SL-1500SH
2000 mm high, 30 - 35° slope - SL-2000SH
2500 mm high, 30 - 35° slope - SL-2500SH
3000 mm high, 30 - 35° slope - SL-3000

Double Width Slides, 1000 mm Wide; Slides Only (SL-XXXXD)
1000 mm high, 30° slope - SL-1000D
1500 mm high, 30° slope - SL-1500D
2000 mm high, 30 - 35° slope - SL-2000D
2500 mm high, 30 - 35° slope - SL-2500D
3000 mm high, 30 - 35° slope - SL-3000D

Double Width Slides, 1000 mm Wide; Slides & Handrail (SL-XXXXDH)
1000 mm high, 30° slope - SL-1000DH
1500 mm high, 30° slope - SL-1500DH
2000 mm high, 30 - 35° slope - SL-2000DH
2500 mm high, 30 - 35° slope - SL-2500DH
3000 mm high, 30 - 35° slope - SL-3000DH

HAGS Stair - Embankment Steps:

Steps single handrail, Steps double handrail
Intended only for embankment installation.

Embankment stair in Option:

2.10 m or 3.00 m without handrail or with one or both sides.

Materials:

Post and stringboard made of oak 45 x 93 x mm.

Stair and handrail made of pine 45 x 93 mm and/or 33 x 120 mm.

Tested according to:

DIN EN 1176-1:2017
EN 1176-1:2017
DIN EN 1176-3:2017
EN 1176-3:2017